



Idemitsu Apollo (Thailand) Co., Ltd.

บริษัท อี데미ตสึ อพอลโล (ประเทศไทย) จำกัด

Chonburi office : 700/623 Moo 4, Amata City Chonburi Industrial Estate, Bankao, Panthong, Chonburi 20160, Thailand Tel: +66 38 456 900

สำนักงานชลบุรี : 700/623 หมู่ 4 นิคมอุตสาหกรรมอมตะซิตี้ชลบุรี ต.บ้านเก่า อ.พานทอง จ.ชลบุรี 20160 โทร +66 38 456 900

Rayong office : 7/467 Moo 6, Amata City Rayong Industrial Estate, Mabyangporn, Pluakdaeng, Rayong 21140, Thailand Tel: +66 38 018 333

สำนักงานระยอง : 7/467 หมู่ 6 นิคมอุตสาหกรรมอมตะซิตี้ระยอง ต.มาบยางพร อ.ปลวกแดง จ.ระยอง 21140 โทร +66 38 018 333

DAPHNE FIRGIST G

1.Application

Daphne Firgist G is a fire-resistant water-glycol type hydraulic fluid, for use in hydraulic systems where oil type hydraulic fluid is liable to cause ignition.

2.Quality

Water, glycol and contain various additives to provide excellent performance.

3.Characteristic

1. Fire resistance.
2. Excellent anti-wear property.
3. High viscosity index.
4. Low pour point.
5. Good vapor phase and liquid phase rust protection.

4. Typical Specification

				ASTM
Density	@15 °C	g/cm3	1.0563	D-1298
Color	ASTM		Red	D-1500
Viscosity	@ 40 °C	mm2/s	46.7	D-445
	@ 100 °C	mm2/s	10.1	D-445
Viscosity Index			212	D-2270
Pour Point		°C	-507	D-97
pH			10.0	-
Copper Corrosion	100°Cx3Hrs.		1a	D-130

- Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provide in the Safety Data Sheet (SDS) are followed.
- SDS is available upon request through your sales contract office, or E-Mail : order@apollothai.com
- Due to continual product research and development, the information contained herein is subject to change without notification.