



Idemitsu Apollo (Thailand) Co., Ltd.

บริษัท อี데미ตสึ อพอลโล (ประเทศไทย) จำกัด

Chonburi office : 700/623 Moo 4, Amata City Chonburi Industrial Estate, Bankao, Panthong, Chonburi 20160, Thailand Tel: +66 38 456 900

สำนักงานชลบุรี : 700/623 หมู่ 4 นิคมอุตสาหกรรมอมตะซิตี้ชลบุรี ต.บ้านเก่า อ.พานทอง จ.ชลบุรี 20160 โทร +66 38 456 900

Rayong office : 7/467 Moo 6, Amata City Rayong Industrial Estate, Mabyangporn, Pluakdaeng, Rayong 21140, Thailand Tel: +66 38 018 333

สำนักงานระยอง : 7/467 หมู่ 6 นิคมอุตสาหกรรมอมตะซิตี้ระยอง ต.มาบยางพร อ.ปลวกแดง จ.ระยอง 21140 โทร +66 38 018 333

DAPHNE PUNCH OIL SU-P2

High performance Punch oil

1. Application

For use on punching and pressing of stainless steel and carbon steel plate in case of the oil existence is undesirable on the progressive work.

2. Quality

Semi-evaporate oil type very low viscosity synthetic oil containing extreme pressure and rust preventive additive.

3. Punching Ability

Optimum Thickness 0.1 – 1.0 mm. For stainless steel, carbon steel and steel alloy.

4. Typical Specification

				<u>ASTM</u>
Density	15 °C	g/cm ³	0.777	D-1290
Color	ASTM		L 0.5	D-1500
Flash Point	P.M.	° C	67	D-92
Viscosity	@ 40 °C	cSt	1.45	D-445
Acid Number		mgKOH/g	0.15	D-972

- Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provide in the Safety Data Sheet (SDS) are followed.
- SDS is available upon request through your sales contract office, or E-Mail : order@apollothai.com
- Due to continual product research and development, the information contained herein is subject to change without notification.