



บริษัท น้ำมันพอลโล [ไทย] จำกัด  
APOLLO (THAILAND) CO.,LTD.



Certificate No. NQ248/00



Certificate No. Q 18558

# DAPHNE MAGPLUS LA-15 (B)

## 1. Application

A non-active sulfur additive water insoluble cutting oil, contain stress releaser additive. Suitable for screw tapping, lathe turning with an excellent cutting ability to prevent uneven gaps between the spiral and good finishing surface. Longer tool life.

## 2. Typical Specifications

Density	@ 15 °C	g/cm <sup>3</sup>	0.8812
Color	ASTM		2.0
Flash Point	(C.O.C.)	°C	176
Viscosity	@ 40 °C	mm <sup>2</sup> /s	15.39
Copper Corrosion	100 °C x 1 Hr.		1 (1b)
Sulfur		wt%	1.34
Fatty Oil		wt%	4.0

Cutting Oil\DN MAGPLUS LA-15 (B).doc

408/154-156 อาคารพอลโยธินเพลส ชั้น 37 ถนนพอลโยธิน พญาไท กรุงเทพฯ 10400

โทร : 0-2619-0330 แฟกซ์ : 0-2619-0260

408/154-156 Phaholyothin Place 37<sup>th</sup> Fl. Phaholyothin Rd., Phayathai Bangkok 10400 Tel : 0-2619-0330 Fax : 0-2619-0260