



Idemitsu Apollo (Thailand) Co., Ltd.

บริษัท อี데미ตสึ อพอลโล (ประเทศไทย) จำกัด

Chonburi office : 700/623 Moo 4, Amata City Chonburi Industrial Estate, Bankao, Panthong, Chonburi 20160, Thailand Tel: +66 38 456 900

สำนักงานชลบุรี : 700/623 หมู่ 4 นิคมอุตสาหกรรมอมตะซิตี้ชลบุรี ต.บ้านเก่า อ.พานทอง จ.ชลบุรี 20160 โทร +66 38 456 900

Rayong office : 7/467 Moo 6, Amata City Rayong Industrial Estate, Mabyangporn, Pluakdaeng, Rayong 21140, Thailand Tel: +66 38 018 333

สำนักงานระยอง : 7/467 หมู่ 6 นิคมอุตสาหกรรมอมตะซิตี้ระยอง ต.มาบยางพร อ.ปลวกแดง จ.ระยอง 21140 โทร +66 38 018 333

DAPHNE CUT HL 25

1. Application

Daphne Cut HL 25 is to be used as a dielectric fluid in electrical discharge machines.

2. Quality

Daphne Cut HL 25 is high quality synthetic lubricating oil.

3. Characteristics

1. This oil is highly refined base oil and odorless.
2. Designed to prevent to be poisoned.
3. Low viscosity and high flash point.
4. As high flash point, this oil is preventable to fire.
5. As good stability, extend oil life.
6. As low viscosity, enables to remove chips easily.

4. Typical Specifications

Density			0.7890
Color	ASTM		L 0.5
Flash Point	P.M.	°C	88
Viscosity	@ 40 °C	mm ² /sec	2.560
Total Acid Number		mgKOH/g	0.01
Distillation	IBP	°C	206
	EP	°C	256

The information in this bulletin is, to our best knowledge, true and accurate, but all recommendation or suggestions are without guarantee since the conditions of use are beyond our control. The manufactures do not accept liability for any loss or damage, however they arise, which results directly from the use of such information. nor do we offer any warranty of immunity against patent infringement.